

Technical data sheet

White Stone Adhesive

Adhesives · 20 kg

**A**

ADHESIVOS

ADHESIVO PEGA PIEDRA BLANCO

Color: Blanco

20 KG

CONTENIDO NETO

ADH-PPI-BLA-020

LOTE: _____ FECHA: _____



FT / FDS

MASCRO

mascro.com.mx

ARTE PRELIMINAR · SACO

PRELIMINARY DOCUMENTATION

Development proposal. Performance and safety await validation.

Commercial identity is adapted to MASCRO. Technical data and pending observations from the source document are retained.

Digital information and pack size

Identification

White Stone Adhesive · Adhesives · Phase 1. Pack size: 20 kg.

Products covered

ADH-PPI-BLA-020 · White · 20 kg

<https://mascro.com.mx/productos/adhesivo-pega-piedra-blanco/>

Identification control

Provisional reference barcode: 111111111111. This is not an assigned GTIN and must not be used to identify or sell the product. Company name, address and telephone numbers remain pending, as in the other drafts.



Description and intended applications

Description

Dry blend of white cement, mineral fillers and additives for developing a tile-installation solution. Tile type, absorption, substrate and service conditions must be confirmed through testing of the specific product.

Product selection

Confirm substrate compatibility, surface preparation, system thickness or consumption and environmental conditions. Do not extrapolate results from other MASCRO products or competitors.

Documentary basis

Existing spreadsheet formulation: FML-008. No unambiguous historical data sheet was found for this pending SKU; a new proposal has been drafted. Performance data from other products are not carried over.

Preparation and application controls

Preparation

First perform a representative test of the substrate and complete system. Record batch identification, temperature, preparation proportions, equipment, time and results. Do not change proportions or add components without technical review.

Trial mixing

Use clean water and an uncontaminated container. Water quantity, resting time, open time and pot life must be determined for this formulation; do not use the dosage of another adhesive or grout.

Acceptance criteria

Appearance or a uniform mix does not demonstrate adhesion, waterproofing, stability or durability. Quantitative criteria must be established before testing and recorded in PLM.

Specifications to validate

Mixing water and consistency

Value and test method: awaiting validation.

Open time and pot life

Value and test method: awaiting validation.

Adhesion and tile compatibility

Value and test method: awaiting validation.

Consumption, curing and service conditions

Value and test method: awaiting validation.

Pack size and storage

20 kg. Keep the container closed and protected from contamination and conditions that could alter its contents. Shelf life must be established through product stability and packaging compatibility studies.

Certifications and warranty

No unsupported certifications or performance classes are published. This draft does not release the product for sale or final application.