

## Technical data sheet

# White Porcelain Tile Adhesive

Adhesives · 20 kg

**A**

ADHESIVOS

**ADHESIVO PORCELÁNICOS BLANCO**

Color: Blanco

**20 KG**

CONTENIDO NETO

ADH-POR-BLA-020

LOTE: \_\_\_\_\_ FECHA: \_\_\_\_\_



FT / FDS

**MASCRO**

mascro.com.mx

ARTE PRELIMINAR · SACO

**PRELIMINARY DOCUMENTATION**

Development proposal. Performance and safety await validation.

Commercial identity is adapted to MASCRO. Technical data and pending observations from the source document are retained.

---

## Digital information and pack size

### Identification

White Porcelain Tile Adhesive · Adhesives · Phase 1. Pack size: 20 kg.

### Products covered

ADH-POR-BLA-020 · White · 20 kg

<https://mascro.com.mx/productos/adhesivo-porcelanicos-blanco/>

### Identification control

Provisional reference barcode: 111111111111. This is not an assigned GTIN and must not be used to identify or sell the product. Company name, address and telephone numbers remain pending, as in the other drafts.



---

## Description and intended applications

### Description

Dry blend of white cement, mineral fillers and additives for developing a tile-installation solution. Tile type, absorption, substrate and service conditions must be confirmed through testing of the specific product.

### Product selection

Confirm substrate compatibility, surface preparation, system thickness or consumption and environmental conditions. Do not extrapolate results from other MASCRO products or competitors.

### Documentary basis

Existing spreadsheet formulation: FML-005. No unambiguous historical data sheet was found for this pending SKU; a new proposal has been drafted. Performance data from other products are not carried over.

---

## Preparation and application controls

### Preparation

First perform a representative test of the substrate and complete system. Record batch identification, temperature, preparation proportions, equipment, time and results. Do not change proportions or add components without technical review.

### Trial mixing

Use clean water and an uncontaminated container. Water quantity, resting time, open time and pot life must be determined for this formulation; do not use the dosage of another adhesive or grout.

### Acceptance criteria

Appearance or a uniform mix does not demonstrate adhesion, waterproofing, stability or durability. Quantitative criteria must be established before testing and recorded in PLM.

---

## **Specifications to validate**

### **Mixing water and consistency**

Value and test method: awaiting validation.

### **Open time and pot life**

Value and test method: awaiting validation.

### **Adhesion and tile compatibility**

Value and test method: awaiting validation.

### **Consumption, curing and service conditions**

Value and test method: awaiting validation.

### **Pack size and storage**

20 kg. Keep the container closed and protected from contamination and conditions that could alter its contents. Shelf life must be established through product stability and packaging compatibility studies.

### **Certifications and warranty**

No unsupported certifications or performance classes are published. This draft does not release the product for sale or final application.