

Technical data sheet

Exterior Acrylic Paint

Paints · 19 L

**P**

PINTURAS

PINTURA ACRÍLICA EXTERIOR

Color: Color por definir

19 L

CONTENIDO NETO

PIN-EXT-CLR-019

LOTE: _____ FECHA: _____



FT / FDS

MASCRO

mascro.com.mx

ARTE PRELIMINAR · CUBETA

PRELIMINARY DOCUMENTATION

Development proposal. Performance and safety await validation.

Commercial identity is adapted to MASCRO. Technical data and pending observations from the source document are retained.

Digital information and pack size

Identification

Exterior Acrylic Paint · Paints · Phase 2. Pack size: 19 L.

Products covered

PIN-EXT-CLR-019 · Color to be defined · 19 L

<https://mascro.com.mx/productos/pintura-acrilica-exterior/>

Identification control

Provisional reference barcode: 111111111111. This is not an assigned GTIN and must not be used to identify or sell the product. Company name, address and telephone numbers remain pending, as in the other drafts.



Description and intended applications

Description

Water-based paint development for exterior architectural surfaces. A white trial base is prepared. Commercial colors will have their own SKUs; this document is not an approved color chart.

Product selection

Confirm substrate compatibility, surface preparation, system thickness or consumption and environmental conditions. Do not extrapolate results from other MASCRO products or competitors.

Documentary basis

Preliminary MASCRO R03 development. No unambiguous historical data sheet was found for this pending SKU; a new proposal has been drafted. Performance data from other products are not carried over.

Preparation and application controls

Preparation

First perform a representative test of the substrate and complete system. Record batch identification, temperature, preparation proportions, equipment, time and results. Do not change proportions or add components without technical review.

Trial application

Mix until uniform and evaluate the application method on a substrate sample. Determine dilution, thickness, number of coats and time between applications through testing. Do not establish coverage or drying time as final values.

Acceptance criteria

Appearance or a uniform mix does not demonstrate adhesion, waterproofing, stability or durability. Quantitative criteria must be established before testing and recorded in PLM.

Specifications to validate

Binder solids and PVC/CPVC

Value and test method: awaiting validation.

pH, viscosity and stability

Value and test method: awaiting validation.

Hiding power, washability and adhesion

Value and test method: awaiting validation.

Density and coverage per applied film

Value and test method: awaiting validation.

Pack size and storage

19 L. Keep the container closed and protected from contamination and conditions that could alter its contents. Shelf life must be established through product stability and packaging compatibility studies.

Certifications and warranty

No unsupported certifications or performance classes are published. This draft does not release the product for sale or final application.